

PRODUCT DETAILS

Category	
Product	SEMI NEW BATCHING PLANT C.64 - 6BINS
Product Order	
Price List	

DESCRIPTION

SEMI NEW BATCHING PLANT C.64 - 6BINS

PRODUCTION THEORIC : 80 Cu.Mtrs./Hour Dry doses

AGGREGATE STORAGE COMPARTMENTS: 90 Cu.Mtrs. with RECONDITIONED PANEL

EXTRACTION: LATERAL ON THE RIGHT

AGGREGATE COMPARTMENTS:

6 nos. compartments

12 nos. batching hatches totally reviewed.

FRAME DIMENSIONS : L 11,8 X 2,40M

AGGREGATE BATCHING:

Totally reviewed aggregate hopper with weighing system provided with 1 no. homologated load cell max. weighing capacity **20.000 kgs.**

Completely reviewed digital display EV2001 with batching automatic system halt on electric comman board.(SOC. COOP. BILANCIAl)

CEMENT BATCHING:

Totally reviewed cement hopper,provided with weighing system with 1 no. homologated load cell max. weighing capacity **5.000 kgs.**

digital display EV 2001 provided with batching automatic system halt also in manual mode on electric command board.

Cement weighing hopper, provided with electro-pneumatic opening through a butterfly valve set in action by an alluminium sheated pneumatic cylinder.

VIBRATORS:

2 nos. vibrator with double bolted plate placed between bottom cones of 2 sand compartments.

1 no. vibrator on aggregate weighing hopper.

1 no. vibrator on cement weighing hopper.

EXTRACTOR BELT:

Extractor Belt totally reviewed with belt 800 mm width.

Extractor belt-related accident prevention system with system halt safety cable and galvanized safety barrier throughout all the lenght.

INCLINED CONVEYOR BELT:

Belt lenght 15.000 mm and width 800 mm.

Conveyor belt carrying structure and hopper to load truck mixer totally reviewed.

Conveyor belt-related accident prevention system with system halt safety cable and galvanized safety barrier throughout all the lenght from 2 mtrs. from ground

SCREW CONVEYOR TO LOAD TRUCK MIXER:

273 mm exterior diameter; 10 mtrs long, **RECONDITIONED.**

WATER BATCHING:

2" electromechanical pulse counter and electropneumatic sphere valve-brand new.

Digital display on electric board provided with automatic system halt also in manual mode-brand new.

CONTROL PANEL:

manuale, **RECONDITIONED**

ELECTRIC PLANT:

RECONDITIONED

AIR COMPRESSED SYSTEM:

1 no. compressor provided with 500 lt tank fixed on lateral side of the frame RECONDITIONED

6 nos. pneumatic cylinders with rapid discharging for the opening of the batching hatches-RECONDITIONED.

1 no. galvanized pipe to supply compressed air to the 6 nos. pneumatic cylinders-RECONDITIONED.

6 nos. 24 V five-way electric valve with to set in action of 6 nos. pneumatic cylinders (batching

hatches)-RECONDITIONED.

PAINTING:

Totally sandblasted, one anti-rust layer and double paint layer quick drying.RAL 6010 GREEN

ADDITIONAL INFORMATION:

Electric installation in frame border with shunt box and **galvanized raceway**.

Electric cables to link the shunt box to control panel. (Longest distance: 30 mtrs.)

WARRANTY: